



ASSEMBLY SYSTEMS 2017/18

www.AIMCO-GLOBAL.com



For over 40 years AIMCO has been working with manufacturers around the world, we are the complete global source for all assembly, fastening, and critical bolting needs. AIMCO can effectively and swiftly meet your needs whether you're in Thailand fastening a 3 mm nut at 3 Nm, or in Tennessee, USA torquing the last lug nut. AIMCO provides the tools and solutions, on a global scale, that guarantee the success of your project. It is with great pride that AIMCO can say the products that we manufacture are **MADE IN THE USA**.

ISO 9001: 2015 Certified

SCREW PRESENTERS: OVERVIEW

For semi-automated assembly, look no further – AIMCO's Acra-Feed screw presenters provide:

PRODUCTIVITY

- One hand operation eliminates manual handling of screws
- Screw is presented to operator for easy magnetic or vacuum pickup
- Keeps workspace clear of dropped fasteners
- Quick feed rate from oscillating hopper design up to two (2) screws per second
- Large hopper holds approximately 1,000 1,500 fasteners
- Solid design no tie downs or straps required

FLEXIBILITY

- Perfect for contract or dedicated assembly
- Switch rails in minutes for different screw sizes

ERGONOMICS



Allows for fewer arm and hand movements

RELIABILITY

- Heavy duty industrial design
- · Modular design for easy repairs

QUALITY

- Uses existing or our new torque control drivers
- Keeps stray fasteners from getting into assemblies





Load screws into the hopper. There is no side to load unit and no gates to limit capacity.



FASTENING IN 3 EASY STEPS

Address screw with magnetized bit.



Acra-Feed[®] Screw Presenter







Bring screw to workpiece and fasten parts.

A-50 SCREW PRESENTERS





A-50BRBTC-4 Compact Robotic Screw Presenter



STANDARD SCREW PRESENTERS

	ADDITIONAL RAIL	SCREV	V SIZE	MAX SCRE	W LENGTH
MODEL	PART NO.	IN	MM	IN	MM
A-50A-0	AR-0	#0	1.4	.39	10
A-50A-1.7	AR-1.7	-	1.7	.39	10
A-50B-1	BR-1	#1	2.0	.75	18
A-50B-2	BR-2	#2	2.3	.75	18
A-50B-3	BR-3	#3	2.6	.75	18
A-50B-4	BR-4	#4	3.0	.75	18
A-50C-6	CR-6	#6	3.5	.75	18
A-50C-8	CR-8	#6-8	4.0	.75	18
A-50C-10	CR-10	#10	5.0	.75	18

Dimensions: 5.1 (W) x 8.5 (L) x 5.3 (H)

Weight: 7.0 lb.

COMPACT ROBOTIC SCREW PRESENTERS

	ADDITIONAL RAIL		IINAL W SIZE	MAX SCREW LENGTH		
MODEL	PART NO.	IN	MM	IN	MM	
A-50ARBTC-0	AR-RBTC-O	#0	1.4	.390	10	
A-50ARBTC-1.7	AR-RBTC-1.7	-	1.7	.390	10	
A-50BRBTC-1	BR-RBTC-1	#1	2.0	.700	18	
A-50BRBTC-2	BR-RBTC-2	#2	2.3	.700	18	
A-50BRBTC-3	BR-RBTC-3	#3	2.6	.700	18	
A-50BRBTC-4	BR-RBTC-4	#4	3.0	.700	18	
A-50CRBTC-6	CR-RBTC-6	#6	3.5	.700	18	
A-50CRBTC-8	CR-RBTC-8	#6-8	4.0	.700	18	
A-50CRBTC-10	CR-RBTC-10	#10	5.0	.700	18	

Dimensions: 7.2 (L) x 4.9 (W) x 5.7 (H) Weight: 6.7 lb.

OPTIONAL ACCESSORIES

MODEL	PART NO.
Mag-O-Net Bit Magnetizer	AM1/4Z, AM5Z, AM3/16Z

ROBOTIC SCREW PRESENTERS

		-		-	
	ADDITIONAL RAIL	SCRE	W SIZE	MAX SCRE	W LENGTH
MODEL	PART NO.	IN	MM	IN	MM
A-50ARBT-0	AR-RBT-O	#0	1.4	.39	10
A-50ARBT-1.7	AR-RBT-1.7	-	1.7	.39	10
A-50BRBT-1	BR-RBT-1	#1	2.0	.70	18
A-50BRBT-2	BR-RBT-2	#2	2.3	.70	18
A-50BRBT-3	BR-RBT-3	#3	2.6	.70	18
A-50BRBT-4	BR-RBT-4	#4	3.0	.70	18
A-50CRBT-6	CR-RBT-6	#6	3.5	.70	18
A-50CRBT-8	CR-RBT-8	#6-8	4.0	.70	18
A-50CRBT-10	CR-RBT-10	#10	5.0	.70	18

Dimensions: 5.1" (W) x 10.8" (L) x 5.3" (H) Weight: 9.2 lb.

WHICH TO USE...?

Standard Screw Presenters

For manual assembly stations where the operator must otherwise pick up and hold fasteners by hand.

Robotic Screw Presenters

For automated fastening systems or manual systems using vacuum assist to pick up non-ferrous fasteners.

Compact Robotic Screw Presenters

For automated systems, or manual systems, using vacuum-assist to pick up nonferrous fasteners when work space is limited,

ACRA-FEED AUTOMATIC SCREW FEED SYSTEMS

Reduces Cycle Time By Approximately Two Seconds Per Fastener

FEATURES AND BENEFITS

- Delivers fastener directly to the driver
- For #2 #10 fasteners, up to 1 inch long
- Available for captive washer type screws (A-315V)
- Feed speed of up to 1 screw per second
- System includes feeder, hose assembly, air screwdriver, and FRL

PRODUCTIVE

- Eliminates reaching for fasteners
- Most jams are easily cleared on the line
- · Frees operator's hand for productive use
- Large hopper holds between 1,000 5,000 fasteners

ERGONOMIC

- Eliminates manual handling of fasteners and shavings
- Reduces workspace clutter
- · Keeps workspace clean of dropped fasteners
- Torque reaction of standard driver is minimal and can be eliminated with optional Ergo-Arm

RELIABLE

- Longest warranty in the industry 3 years
- Rocking Bar design only operates as needed
- "Photo eyes" maximize motor life
- Design eliminates burrs and shavings by minimal handling of the fastener
- Durable head assembly lasts for years
- There are more Acra-Feed systems in use than any other system

	APPLICABLE	SCREW	LENGTH				DIMENSIONS
MODEL	SCREWS	IN	MM	HOPPER CAPACITY	MAX FASTENING SPEED	WEIGHT (LB)	L X W X H (IN)
A-2100 Series	M2-M5 (#2 - #10)	1/4-1	6-25	1,500cc (1,000-5,000 pcs)*	60 screws/min*	68	7 x 17 x 16
A-315V Series	M2-M5 (#2 - #10)	1/4-1	6-25	450cc (500-2,500 pcs)*	60 screws/min*	74	10 x 21 x 16

* Dependent on screw size

HOW TO ORDER: Acra-Feed systems are application-specific and configured to the unique workpiece and requirements of the user. Quotations are provided from a review of sample workpieces, 25 fasteners, and required torque specifications.





Delivery Hose: 10 ft Air Pressure: 85 psi Power: AC 110V, 20W, AC 220V by request. Contact AIMCO at 1-503-254-6600, or toll free 1-800-852-1368.

NOTES

AIMCO CORPORATE HEADQUARTERS 10000 SE Pine Street Portland, Oregon 97216 Phone: (503) 254–6600 Toll Free: 1-800-852-1368

AIMCO CORPORATION DE MEXICO SA DE CV Ave. Cristobal Colon 14529 Chihuahua, Chihuahua. 31125 Phone: (01-614) 380-1010 Fax: (01-614) 380-1019

> AIMCO SOUTH AMERICA Carrera 29A, #7B-91. Origami Building. Int604. Medellin; Colombia 050021

AIMCO EUROPE Dibao Plaza Avenida Río Gallo, 431 19174 Galápagos - Guadalajara Spain Phone: +34 673 34 99 25

AIMCO CHINA Room 607, No. 3998 Hongxin Rd Minhang District, Shanghai China Phone: 0086-21-34319246 Fax: 0086-21-34319245

> AIMCO SOUTH KOREA B-1213, 167, Songpa-Daero Songpa-Gu, Seoul 05800 South Korea Phone: 0082-2-2054-8930 Cell: 0082-10-9804-8905

