















CUSTOMER TO CHOOSE MOUNTING OPTION.
MOUNTING PLINTH (PART NO. 27816) IS SHOWN.



	DOCUMENT CONTROL PRINTED COPIES OF THIS DOCUMENT ARE CONSIDERED TO BE UNCONTROLLED DOCUMENTS. HOLDERS ARE RESPONSIBLE FOR VERIFYING THE CURRENT REVISION LEVEL WITH PURCHASING OR ENGINEERING PRIOR TO USE OR FABRICATION. THE CONTROLLED VERSION OF THIS DOCUMENT IS ELECTRONICALLY MAINTAINED.	
®	PROPRIETARY AND CONFIDENTIAL THIS DRAWING CONTAINS INFORMATION STRICTLY CONFIDENTIAL TO ACRADYNE/AIMCO. IN THE ABSENCE OF THE PROPRIEMENT OF THE	
	OF EXPRESSED WRITTEN PERMISSION, ACRADYNE/AIMCO HAS LOANED THIS COPY WITH THE MUTUAL UNDERSTANDING THAT (A) IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAN FOR THAT IN WHICH IT WAS PROVIDED, (B) THE DATA CONTAINED HEREIN WILL NOT BE DISCLOSED TO OTHERS, (C) IT WILL NOT BE REPRODUCED, AND (D) IT WILL BE RETURNED	F
	TO ACRADYNE/AIMCO IMMEDIATELY UPON DEMAND.	

	REVISION BLOCK					
A NED	REVISION LEVEL	REVISION RELEASE DATE	DESCRIPTION OF CHANGES MADE TO PART	ECN#	AUTHOR/ APPROVAL	DRAWING
) NG						REMOV MACHIN
						.X = ±.030
BE FOR OR LED ED.						UN E DIMENS SU
	T T					

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES
IENSIONS AND TOLERANCING PER ANSI Y14.5
SURFACE ROUGHNESS PER ANSI Y14.36

CONTROLLER ASSY W/O TOUCHSCREEN & I/O

BLOCK TOLERANCING PER DECIMAL: ±.030 .XX = ±.010 .XXX = ±.005 .XXXX = ±.0005 ANGLE = ±0°30'

ANGLE = ±0° 30'

REMOVE BURRS AND SHARP EDGES: R.015 MAX MACHINE SURFACE FINISH: 125 RMS OR BETTER

DRAWINGS AND TECHNICAL DOCUMENTS CONTROLLED BY:

ACRADYNE MECHANICAL ENGINEERING

SCAI

CONIKOLLER ASSI	W/O IOUCHSCREEN & I/O
	GEN 4

Έ	PART / DRAWING NUMBER		REVISION
	iEC4E_		В
CALE 1:4	DO NOT SCALE DRAWING	SH	EET 2 OF 2