



## Service Bulletin

**Bulletin # SB00034**

# OneToo – Moment Alpha – Bluetooth Pairing Instructions

Authors: Michael Schnell

Date: October 18, 2018

### Introduction

The Moment Alpha wrench/controller kit requires a Bluetooth signal to operate effectively. Below are steps to pair them via Bluetooth

### Equipment/Software

- CPSKV00 – Wrench Handle with battery
- Bench mount or Portable tablet

### Hardware Setup

- Power on the bench mount or portable tablet
- Power on CPSKV00 Wrench Handle

10000 SE Pine Street

Portland, OR 97216

TEL: 800.852.1368

FAX: 503.262.3410

[www.aimco-global.com](http://www.aimco-global.com)

## Tool Setup

### Recommended Basic Settings

The wrench handle and tablet are paired via Bluetooth and these steps will assure that communication is working properly

1. With controller and wrench handle powered up – set the handle on a flat surface without attachments

Touch 'Reconnection' to connect wrench handle with tablet > Press OK to verify



Syncing is complete when the **Reconnection** image is replaced by an image of a wrench handle on the screen. If the wrench handle image does not appear, go to step 2

2. **Add or verify wrench ID to Controller**

Pull battery from wrench handle and locate the (4) digit ID on the inside wall of the battery housing

Touch the menu button > Touch Connection & Backup

**Sign in** IF the pencil is visible in the top right corner of the screen.



Touch the pencil and entering user name and password

User name: **admin** Password: **admin**

10000 SE Pine Street

Portland, OR 97216

TEL: 800.852.1368

FAX: 503.262.3410

www.aimco-global.com



From the Connection & Backup screen, Touch 'Wrench' and enter or validate the (4) digit wrench handle number

Test the connection – from the main menu, repeat step 1 above by touching the 'reconnection' image while the wrench handle is laying flat with no attachment. This is the final step for bench mount controller pairing. Further steps may be necessary for the portable tablet, see below.

10000 SE Pine Street

Portland, OR 97216

TEL: 800.852.1368

FAX: 503.262.3410

www.aimco-global.com

### Pair Wrench in Android Tablet Settings > Bluetooth

Go to setting in tablet > swipe down from top to touch 'setting' icon

Touch 'Connections'

Touch 'Bluetooth'

Turn on Bluetooth and look for available devices

Unpair any existing paired devices that are not the wrench handle being paired at this time

With wrench handle on – you will see the device 'AlphaTooOne\_XXXX'

Enter device PIN code. This code is the inverse of the wrench ID. See example below:

The code PIN of the wrench is the ID wrench but Inverse like this  
ID wrench = 0145 => PIN = 4501

Navigate back out of settings by touching the return arrow symbol imbedded on the side of the tablet until the OneToo system appears

### Restart tablet

Upon re-boot, touch the reconnection space while the wrench handle is on

Connectivity is confirmed when the wrench handle is visible in upper right corner of the tablet as shown in image

