

# AcraDyne®

## Hold & Drive Nutrunners



### FEATURES AND BENEFITS

- Torque range from 20Nm - 200Nm.
- Durable, cutting edge design.
- Standard 1" and 2" travels.
- Custom to order sockets and holders.



**AIMCO**

**800-852-1368**

**www.aimco-global.com**

phone: 503-254-6600

fax: 503-255-2615

MODEL *	NM	MAX TORQUE	FT-LB	NM	TORQUE RANGE	FT-LB	FREE SPEED RPM	WEIGHT LB	MIN/MAX SOCKET
AEH4F12020B-(1,2)	20	14.75	14.75	4 - 16	3.0 - 11.8	3.0 - 11.8	533	-1=2.8, -2=3.0	9/16 (14MM) / 13/16, (21MM)
AEH4F12026B-(1,2)	26	19.18	19.18	5.2 - 20.8	3.8 - 15.4	3.8 - 15.4	432	-1=2.8, -2=3.1	9/16 (14MM) / 13/16, (21MM)
AEH32025B-(1,2)	25	18.44	18.44	5 - 20	3.7 - 14.8	3.7 - 14.8	833	-1 = 3.5, -2 = 3.5	9/16 (14MM) / 13/16, (21MM)
AEH32030B-(1,2)	30	22.13	22.13	6 - 24	4.4 - 17.7	4.4 - 17.7	803	-1 = 3.5, -2 = 3.6	9/16 (14MM) / 13/16, (21MM)
AEH32040B-(1,2)	40	29.50	29.50	8 - 32	5.9 - 23.6	5.9 - 23.6	574	-1 = 3.5, -2 = 3.7	9/16 (14MM) / 13/16, (21MM)
AEH33053B-(1,2)	53	39.09	39.09	12 - 48	8.9 - 35.4	8.9 - 35.4	1095	-1=5.6, -2=5.8	9/16 (14MM) / 13/16, (21MM)
AEH33060B-(1,2)	60	44.25	44.25	12 - 48	8.9 - 35.4	8.9 - 35.4	845	-1=7.3, -2=7.5	5/8 (16MM) / 1-1/4, (32MM)
AEH33090B-(1,2)	90	66.38	66.38	18 - 72	13.2 - 53.1	13.2 - 53.1	568	-1=7.3, -2=7.6	5/8 (16MM) / 1-1/4, (32MM)
AEH33120B-(1,2)	120	88.51	88.51	24 - 96	17.7 - 70.8	17.7 - 70.8	442	-1=10.0, -2=10.3	5/8 (16MM) / 1-1/4, (32MM)
AEH33200B-(1,2)	200	147.51	147.51	40 - 160	29.5 - 118	29.5 - 118	245	-1=10.0, -2=10.4	5/8 (16MM) / 1-1/4, (32MM)
AEH35140B-(1,2)	140	103.26	103.26	35 - 140	25.8 - 103.3	25.8 - 103.3	472	-1=10.6, -2=11.0	5/8 (16MM) / 1-1/4, (32MM)
AEH35175B-(1,2)	175	129.1	129.1	44 - 175	32.5 - 129.1	32.5 - 129.1	384	-1=10.6, -2=11.1	5/8 (16MM) / 1-1/4, (32MM)

\* Add "1" to part numbers for 1" travel. Add "2" to part numbers for 2" travel.