



Uryu BP-T Series Battery Oil Pulse Tools

“Operator First” design means a lighter-weight, ergonomic pulse tool

- Direct Power Train and High-Efficiency Brushless Electric Motor deliver reduced noise and vibration
- Hydraulic Impulse Unit delivers reaction-free tightening
- Cooling fan improves heat management, increasing duty cycle up to 20% over the UDBP-TA series
- High-capacity Li-Ion battery pack provides up to 20% more fastener runs per charge than the UDBP-TA series
- The Ergonomic Handle coupled with a Compact Design provides an improved user experience



MODEL*	CAPACITY (NOMINAL BOLT SIZE)		TORQUE RANGE		FREE SPEED	OVERALL LENGTH		WEIGHT W/O SOCKET BIT				FROM CENTER TO OUTSIDE		SQ. DR OR HEX SIZE		SOUND PRESSURE LEVEL (LpA) dB(A)	BATTERY VOLTAGE (CAPACITY)
	MM	IN	NM	FT-LB		MM	IN	KG	LB	KG	LB	MM	IN	MM	IN		
BP-T40-(B)(KIT)	5	No. 10	4.5-8	3.3-5.9	3,300	197	7.8	1.4	3.08	1.15	2.53	27	1.1	9.5 Hex	3/8 Sq.	75	10.8V (2.0Ah)
BP-T40D-(B)(KIT)	5	No. 10	4.5-8	3.3-5.9	3,300	200	7.9	1.4	3.08	1.15	2.53	27	1.1	6.35 Hex	1/4 Hex	75	10.8V (2.0Ah)
BP-T50-(B)(KIT)	6-8	1/4-5/16	7-15	5.1-11.1	3,900	197	7.8	1.4	3.08	1.15	2.53	27	1.1	9.5 Sq.	3/8 Sq.	76	10.8V (2.0Ah)
BP-T50D-(B)(KIT)	6-8	1/4-5/16	6.5-13	4.8-9.6	3,900	200	7.9	1.4	3.08	1.15	2.53	27	1.1	6.35 Hex	1/4 Hex	76	10.8V (2.0Ah)
BP-T60-(B)(KIT)	8	5/16	13-26	9.6-19.2	4,800	202	8.0	1.6	3.52	1.25	2.75	27	1.1	9.5 Sq.	3/8 Sq.	76	14.4V (2.0Ah)
BP-T60D-(B)(KIT)	8	5/16	13-26	9.6-19.2	4,800	205	8.1	1.6	3.52	1.25	2.75	27	1.1	6.35 Hex	1/4 Hex	77	14.4V (2.0Ah)

* Base models come with no battery. Batteries are available separately or in tool/kits combinations.
 Add "B" to end of the model number to order a tool with one (1) battery.
 Add "KIT" to the end of the model number to order a tool kit, which includes one (1) tool, two (2) batteries, and one (1) battery charger.

BATTERIES AND BATTERY CHARGER

BATTERY MODEL #	DESCRIPTION	VOLTAGE	TYPE	CAPACITY
EYFB32	Battery for BP-T40, BP-T40D, BP-T50, and BP-T50D	10.8V	Li-Ion	2.0Ah
EYFB41	Battery for BP-T60 and BP-T60D	14.4V	Li-Ion	2.0Ah


CHARGER MODEL #	DESCRIPTION	WEIGHT	INPUT VOLTAGE	DIMENSIONS	BATTERY CAPACITY
EYOL82B	Li-Ion battery charger	0.93 kg (2.0 lbs)	120VAC	9.3" D x 7.1" W x 3.6" H	3.0 - 4.2Ah



EYFB32



EYFB41



EYOL82B



CORPORATE HEADQUARTERS
 10000 SE Pine Street
 Portland, Oregon 97216
 Phone: (503) 254-6600
 Toll Free: 1-800-852-1368

AIMCO CORPORATION
 DE MEXICO SA DE CV
 Ave. Cristobal Colon 14529
 Chihuahua, Chihuahua. 31125
 Mexico
 Phone: (01-614) 380-1010
 Fax: (01-614) 380-1019

AIMCO EUROPE
 Dibao Plaza Avenida Río Gallo, 431
 19174 Galápagos - Guadalajara
 Spain
 Phone: +34 673 34 99 25

AIMCO CHINA
 Room 607, No. 3998 Hongxin Rd
 Minhang District, Shanghai
 China
 Phone: 0086-21-34319246
 Fax: 0086-21-34319245

AIMCO SOUTH KOREA
 B-1213, 167, Songpa-Daero
 Songpa-Gu, Seoul 05800
 South Korea
 Phone: 0082-2-2054-8930
 Cell: 0082-10-9804-8905

AIMCO SOUTH AMERICA
 Carrera 29A, #7B-91,
 Origami Building, Int604,
 Medellín, Colombia 050021

Rev. 07-18
 Printed in USA
 ©2018 AIMCO